

ENERGY, SOUND, AND IMPACT (INSULATION) CERTIFICATE

INFORMATION	
PERMIT NUMBER:	
JOB ADDRESS:	
STATEMENT OF COMPLIANCE	
WE, THE UNDERSIGNED, HEREBY CERTIFY THAT THE ENERGY, SOUND, AND IMPACT INSULATION HAS BEEN INSTALLED IN THE ABOVE REFERENCED PROJECT, IN COMPLIANCE WITH THE \Box CURRENT OR \Box (YEAR) EDITION OF THE FLORIDA BUILDING CODE, THE APPROVED ENERGY CALCULATIONS AND PLANS AND IN ACCORDANCE WITH GOOD CONSTRUCTION PRACTICE. THE INSULATION FURNISHED AND INSTALLED HAS THE CHARACTERISTICS SHOWN BELOW: (CHECK ALL APPLICABLE BOXES).	
NOTE: FOR LIGHTWEIGHT INSULATING CONCRETE, USE APPROPRIATE FORMS, SEPARATE FROM THIS ONE.	
1) EXTERIOR CBS WALLS INSULATION: R(MIN); MATERIAL:; THICKNESS:INCH(I	ES);
2) EXTERIOR FRAME/METAL STUD WALL: R(MIN); MATERIAL:; THICKNESS:INCH(I	ES);
☐ 3) EXTERIOR SOLID CONCRETE WALLS: R(MIN); MATERIAL:; THICKNESS:INCH(I	ES);
4) INTERIOR WALLS SEPARATING A/C FROM NON-A/C SPACES INSULATION R	ON: ES);
☐ 5) MULTI-FAMILY RESIDENTIAL ONLY: THE COMMON (PARTY) WALLS TO TWO SEPARATE CONDITIONED TENANCIES SHALL BE INSULATED TO A MIN. OF R-11 FOR FRAME WALLS, AND TO R-3 ON BOTH SIDES OF COMMON MASONRY WALLS.	
SEE THE \square CURRENT OR \square (YEAR) EDITION OF THE ENERGY CODE. THESE "MINIMUM LEVELS OF INSULATION" ARE NOT INCLUDED IN THE ENERGY CALCULATIONS BUT SHALL BE INSTALLED IN THE FIELD.	
☐ 6) CEILING INSULATION: R(MIN); MATERIAL:; THICKNESS:INCH(I	ES); DENSITY:LB/FT; MFGR:
□ 8) FLOOR/CEILING ASSEMBLIES BETWEEN DWELLING UNITS OR BETWEEN DWELLING UNITS AND PUBLIC OR SERVICE AREAS SUCH AS HALLS, CORRIDORS, STAIRS, ETC. MUST HAVE AN IMPACT INSULATION CLASS (IIC) RATING OF NOT LESS THAN 50.	
SIGNATURES	
INSTALLED BY: (INSULATION COMPANY NAME)	(INSIII ATION CONTRACTOR SIGNATURE)
	(INSULATION CONTRACTOR SIGNATURE)
INSULATION CONTRACTOR CC#: DA	ATE CERTIFIED:
0.C./BUILDER:	
(COMPANY NAME)	(G.C./BUILDER'S SIGNATURE)
INSULATION CONTRACTOR CC#: DA	ATE CERTIFIED: